


Zakład Usługowo-Projektowy  93-412 Łódź, ul. Barwna 12		Komora K-705					str/z 1/1	
		PT podpór tymczasowych					rew./rev. 0	
		Specyfikacja elementów stalowych					nr/No	1699-02
Poz. Item	Profil Profile		Dł. 1 elem. Lenght of 1 elem.	Ilość Quantity	Długość Lenght	Masa jedn. Elem.mass	Masa Mass	Uwagi Remarks
			mm	szt./pcs.	m	kg/m	kg	
PODPORA T1			T1	szt./pcs.	1	Rys./Dwg.		K 4
1	C120		2400	1	2,4	13,40	32,2	
2	☞ 10 x 100		146	2	0,3	7,85	2,3	
3	☞ 10 x 80		108	2	0,2	6,28	1,4	
4	C120		1490	4	6,0	13,40	79,9	
5	☞ 10 x 95		170	4	0,7	7,46	5,1	
6	C120		300	2	0,6	13,40	8,0	
7	☞ 10 x 50		12	8	0,1	3,93	0,4	
8	C120		860	2	1,7	13,40	23,0	
9	C120		2222	4	8,9	13,40	119,1	
10	☞ 10 x 95		274	4	1,1	7,46	8,2	
11	☞ 10 x 115		240	4	1,0	9,03	8,7	
K1	kotwa  HST-3	M 10 x 120		28		0,0800	2,2	
Razem/Total						290,4		
PODPORA T2			T2	szt./pcs.	1	Rys./Dwg.		K 5
12	C120		540	2	1,1	13,40	14,5	
13	C120		1438	2	2,9	13,40	38,5	
14	C120		670	1	0,7	13,40	9,0	
15	C120		1677	2	3,4	13,40	44,9	
9	C120		2222	4	8,9	13,40	119,1	
10	☞ 10 x 95		274	4	1,1	7,46	8,2	
11	☞ 10 x 115		240	2	0,5	9,03	4,3	
16	☞ 10 x 35		120	8	1,0	2,75	2,6	
K1	kotwa  HST-3	M 10 x 120		28		0,0800	2,2	
Razem/Total						243,4		
PODPORA T3			T3	szt./pcs.	1	Rys./Dwg.		K 5
17	C120		500	2	1,0	13,40	13,4	
18	C120		1587	2	3,2	13,40	42,5	
19	C120		630	1	0,6	13,40	8,4	
20	C120		1718	2	3,4	13,40	46,0	
11	☞ 10 x 115		240	2	0,5	9,03	4,3	
16	☞ 10 x 35		120	4	0,5	2,75	1,3	
K1	kotwa  HST-3	M 10 x 120		28		0,0800	2,2	
Razem/Total						118,3		
ŻEBRO PUNKTU STAŁEGO			PS	szt./pcs.	1	Rys./Dwg.		K 5
30	☞ 10 x 65		65	16	1,0	5,10	5,3	
Razem/Total						5,3		